




# GXCAN15

350+ Amp 12-800 Vdc  
Automatic-Trip, Over-Current Contactor  
with CAN-BUS Communication



## FEATURES

- > Chassis level power terminals – No need for specially routed power cables, special bus bars, or special lugs.
- > Rugged **EPIC®** seal rated to 175°C – Reduced risk of fire or meltdown in over current conditions. The same technology used for advanced aerospace programs.
- > Hermetically sealed – Designed to meet: UL1604 for Class I & II, Div 2 and Class III for use in hazardous locations, IP67 for temporary water immersion for 30 min, IP69K for pressure washing, SAE J1171 - external ignition protection, and ISO8846 for protection against ignition around flammable gasses.
- > High Efficiency Dual DC Coils – Very low 12 or 24 VDC continuous coil power with no EMI emissions or cross-talk on your system control power. Ideal for battery powered systems or where low power is needed.
- > Built-in coil suppression for all DC coils – Saves you engineering time and parts cost to add external coil suppression.
- > Stainless steel nuts and mounting inserts, for years of corrosion free service.
- > Not position sensitive – can be mounted in any position for ease of installation.


ADVANCED SWITCHING SOLUTIONS

## PRODUCT SPECIFICATIONS

Specifications	Units	Data
Contact Arrangement	Form X	SPST-NO
Mechanical Life	Cycles	1,000,000
Contact Resistance <sup>1</sup>		
Max	mohms	0.4
Typical	mohms	0.15 to 0.3
Operate Time <sup>2</sup>		
Max	ms	20
Typical	ms	13
Release Time, Max	ms	12
Insulation Resistance <sup>3</sup>	Mohms	100
Dielectric at Sea Level (Leakage < 1mA)	VRMS	2,200
Shock, 1/2 Sine, 11ms	G peak	20
Vibration, Sinusoidal (500-2000 Hz Peak)	G	15
Ambient Temp Range		
Operating <sup>4</sup>	°C	-55 to +85
Storage	°C	-70 to +150
Weight, Typical	Kg (Lb)	0.73 (1.6)
Environmental Seal	Exceeds IP67 & IP69K	
Salt Fog	MIL-STD-810	

## POWER SWITCHING AND CURRENT CARRY RATINGS

DC POWER SWITCHING CYCLES<sup>8</sup>




## COIL RATINGS


(25°C, Currents & Power At Nominal V)

Coil P/N Designation	B	C
Coil Voltage (Nominal)	12 VDC	24 VDC
Coil Voltage (Max)	16 V	32 V
Coil Voltage (Min) <sup>5, 7</sup>	9 V	17 V
Inrush Current (Max) <sup>5, 6</sup>	3.9 A	1.6 A
Hold Current after Inrush (Max) <sup>6</sup>	0.23 A	0.097 A
Coil Hold Power (Max) <sup>6</sup>	2.8 W	2.3 W
Coil Back EMF <sup>9</sup>	0 V	
Transients on Power Pins (2, 7)	+50 V, 13 ms	
Vin Power Pins (2, 7) Reverse Polarity (Max)	-80 V	

CURRENT CARRY vs TEMPERATURE  
with 4/0 AWG (120 mm<sup>2</sup>) conductor



## DIMENSIONS



### Control and Communication

To enable internal 120ohm CAN termination:  
 Jumper Pin1 and Pin5.  
 See Notes & Definitions **10**.

### Mounting

M6 Bolts

### Case Material

DuPont Zytel FR50  
 (25% Glass Filled Nylon)

### Power Connection



Zinc Plated M12x1.75 Bolt  
 Stainless M12x1.75 Flanged Nut

Torque 23-34Nm [200-300in-lb]


### Mating Connector

Gigavac offers the required mating connector as an assembled unit ([0857-9/10](#)) or as a component package, see Accessories.

Deutsch Connector Housing P/N: DT06-08SA  
 Solid Contact Socket P/N: 0462-201-16141  
 Wedge Lock P/N: W8S  
 Sealing Plug P/N: 114017  
 Crimp Tool P/N: HDT-48-00



### Power Contacts



CANH and CANL comply with CAN-BUS specification

## PART NUMBER SYSTEM

GXCAN15	B	E	X	J	V
Coil Voltage	B = 12 Vdc, Internal Coil Suppression C = 24 Vdc, Internal Coil Suppression				
Coil Termination		E = 8 Pin Deutsch Connector			
Auxiliary			X = None B = SPST, NO		
Communication				J = J1939	
Voltage Sensing					X = None V = Sensing

## APPLICATION NOTES

- Power switching lifecycles are based on [current flow](#) from A2(+) to A1(-). For best breaking performance, the contactor should be installed so that current flows from A2(+) to A1(-). There are cases where the contactor will interrupt power in the opposite direction but please contact GIGAVAC to confirm suitability. Direction of current flow is not relevant during make or when flowing on closed contacts. For bi-directional contactors, please contact GIGAVAC.
- Applications with [capacitors](#) will require a pre-charge circuit.
- Electrical life rating is based on resistive load with 27μH maximum inductance in circuit. Because your application may be different, we suggest you test the contactor in your circuit to verify life is as required.
- End of life is defined as when the dielectric, insulation resistance or contact resistance fails the specifications listed.

## SETTINGS PARAMETERS

Parameter	Units	Data
Current Trip Setting Range	A	±(20-600)
Current Sense Accuracy		±7%
Over Current Response Time	ms	2ms + release time

### Notes & Definitions:

- Contact resistance measured at currents higher than 100A.
- Operation time is measured at 25°C and includes maximum 7ms bounce.
- Insulation resistance is 50 Mohms after life.
- Contactor can operate up to 125°C in special cases - contact GIGAVAC for details.
- [Contactor has two coils.](#) Both are used for pick-up, and then in approximately 75 milliseconds, one coil is electronically removed from the coil drive circuit. The remaining coil supplies low continuous hold power sufficient for the contactor to meet all of its specified performance specifications. This provides low coil power without PWM electronics that can cause EMI emissions and/or cross-talk on control power.
- Contactor is operated by a coil that changes resistance with temperature. Since inrush current, hold current and coil hold power are specified at nominal voltage, they will be lower than indicated at temperatures above 25°C and higher than indicated at temperatures below 25°C. Similarly, pick-up and drop-out voltages will be higher than indicated at temperatures above 25°C and lower than indicated at temperatures below 25°C.
- For pick-up testing of contactors with dual coils, the voltage can not be ramped up slowly, but must be applied instantly to at least the maximum pick-up voltage. Otherwise, the contactor will not pick-up.
- Limit make current to 600A to avoid contact welding. For AC power switching cycles, contact factory.
- Coils are switched internally with a FET, so no fly-back/suppression voltage is seen at the coil inputs.
- Control and Communication  
Protocol: J1939  
Features:
  - Read: device ID, firmware version, current, temperature, contactor cycle-log and optional contact-volts sensing.
  - Read/Write: power supply under-voltage-shutoff, contactor (open/close), trip points, trip delays, power up default (open/close).
  - Contact GIGAVAC for CAN-BUS communication protocol details.